

# MANITOWOC MLC100-1

Crane Specifications	
<b>CAPACITY</b>	<ul style="list-style-type: none"> <li>110 ton load rating</li> </ul>
<b>BOOM</b>	<ul style="list-style-type: none"> <li>Independent boom hoist, single drum grooved for 0.75 inch diameter wire rope</li> <li>150 ft main boom</li> </ul>
<b>RATED CAPACITY LIMITER (RCL)</b>	CCS two full graphic displays, travel and swing alarms, RCL/RCI (Rated Capacity Limiter/Rated Capacity Indicator) system
<b>OPERATOR'S CAB</b>	Enclosed galvaneeded steel insulated with sliding door, safety glass windows, horn, heater, front and roof windshield wipers, AC, dome light, sun visor and shade, fire extinguisher, fan
<b>SWING</b>	Single swing drive, planetary reduction with internal brake. Max swing speed 2.5 rpm.
<b>COUNTERWEIGHT</b>	Series 1 upper counterweight: 45,450 lb Series 2 upper counterweight: 73,020 lb Series 2 carbody counterweight: 23,150 lb
<b>HYDRAULIC SYSTEM</b>	Three high pressure pumps. 83 gallon reservoir capacity.
<b>ENGINE</b>	Cummins QSB 6.7L Tier 4 Final, 6 cylinder diesel, 300 HP
<b>HOOK BLOCK</b>	13.8 ton headache ball 93.7 ton three sheave hook block
<b>ADDITIONAL FEATURES</b>	<ul style="list-style-type: none"> <li>Cold weather package</li> <li>Wind speed indicator</li> <li>Boom top position light</li> </ul>

