

# NATIONAL CRANE NBT60L

**Capacity:** 54.4 t (60 US)

**Main Boom:** 46 m (151 ft)

**Tip Height:** 49.1 m (161 ft)



## NATIONAL CRANE®

### Crane Specifications

<b>BOOM</b>	<ul style="list-style-type: none"><li>• 11.1 m - 46 m (36.5 ft - 151 ft) five-section boom</li><li>• Max tip height of 49.1 m (161 ft)</li><li>• Multi-stage hydraulic cylinder and cable operation, four-plate, high-strength steel construction, three-sheave, quick reeve boom nose, Easy-Glide wear pads.</li></ul>
<b>BOOM ELEVATION</b>	One double-acting hydraulic cylinder (-8° to 80°) with integral holding valve.
<b>RCL &amp; ATB SYSTEMS</b>	Graphical display capacity limiter and ATB system with audio-visual warning and crane lockout function, Work Area Definition System (WADS), Outrigger Monitoring System (OMS).
<b>CAB</b>	Tilting cab from horizontal to +20°, tinted safety glass, fixed front window with windshield wiper and washer, sliding skylight window with windshield wiper, sliding left side glass door, sliding right side window w/safety grille, tilting rear window, four-way adjustable, cushioned/heated seat & armrests with seatbelt, heater, AC, fan, bubble level, adjustable sun visor, dome light, cup holder, fire extinguisher, load chart binder
<b>COUNTERWEIGHT</b>	Hydraulically removable counterweight system.
<b>SWING</b>	360° rotation using (1) low speed high torque motor with manually adjustable swing adjustment valve.
<b>HYDRAULIC SYSTEM</b>	Hydraulic accessory manifold, boom mounted hydraulic hose reel, pressure intensifier manifold in platform.
<b>OUTRIGGERS</b>	Out and down outriggers



For additional information, please contact  
**Bruce Austin at (443) 962-0746 or**  
**[Jaime.Cook@mgxequipment.com](mailto:Jaime.Cook@mgxequipment.com).**

*Crane available subject to prior sale.*