

GROVE GHC220

Capacity: 200 t (220 USt)

Main Boom: 56.4 m (185 ft)



GROVE®



| Crane Specifications | |
|---|--|
| MAIN BOOM | <ul style="list-style-type: none">• 13.1 m - 56.4 m (43 ft - 185 ft) six-section boom• Max tip height: 58 m (190.3 ft)• Boom elevation -3° to 80° |
| EXTENSIONS | <ul style="list-style-type: none">• Boom extension: 10.6 m - 16.2 m - 21.8 m (34.8 ft - 53.1 ft - 71.5 ft) offsettable swingaway• Boom extension max tip height: 81 m (265.7 ft)• Heavy-duty jib extension: 5 m (16.4 ft) offsettable at 0°, 20°, 37° |
| RATED CAPACITY LIMITER & ANTI-TWO BLOCK SYSTEM | Graphical display of load moment and anti-two block system with audio-visual warning and control lever lock-out. |
| CAB | Large capacity operator's compartment, air suspended operator's seat with lumbar support, heated seat, headrest, 3" safety belt, ergonomic control panels, load sensing electric dual axis joystick controls, travel pedals and levers, exceptional sound insulation, sliding door & window, tinted safety glass, front tilt window, large skylight with sun protection, windshield and roof wiper/washer system, Bluetooth/AM/FM/USB/MP3 radio, climate control, fire extinguisher, 20° tilt capability. 7" monitor for rear view, right side, and hoist cameras. |
| SWING | Two-speed, compact planetary gear, 360° continuous rotation. 0-1.6 rpm variable swing speed. |
| ENGINE | Cummins B 6.7 L (Tier IV final), 6-cylinder diesel, 194 kW (260 bhp). |
| MISCELLANEOUS EQUIPMENT | <ul style="list-style-type: none">• Central, easily accessible lubricating strip• Grated platforms• Service friendly engine and hydraulic compartment• 100 t (110 USt) 3-sheave quick reeve hook block• External RCL light bar• Storage box attached to carbody counterweight |

For additional information, please call
Bruce Austin at (443) 962-0746
or email Jaime Cook at
Jaime.Cook@mgxequipment.com.

Crane available subject to prior sale.