

# GROVE GMK5200-1

**Capacity:** 200 t (240 USt)

**Main Boom:** 64 m (210 ft)



## GROVE®



Crane Specifications	
<b>BOOM</b>	<ul style="list-style-type: none"> <li>13.7 m - 64 m (44.9 ft - 210 ft) 6-section boom w/ TWIN-LOCK™ pinning system</li> <li>67 m (219 ft) maximum tip height</li> <li>-1.5° to 82° boom angle</li> </ul>
<b>ENGINE</b>	Mercedes Benz OM471LA (390 kW / 532 HP)
<b>LOAD MOMENT/ ANTI-TWO BLOCK</b>	Load moment and independent anti-two block system with audio visual warning and control lever lock-out
<b>DRIVE/STEER</b>	10 x 6 x 10 / all wheel steering
<b>TRANSMISSION</b>	Mercedes G280 16 gears forward, 2 reverse, 1-stage transfer case with secondary water retarder
<b>SUSPENSION</b>	MEGATRAK™ all wheel independent hydropneumatic suspension and hydraulic lockout
<b>OUTRIGGERS</b>	4 double hydraulically telescoping beams with vertical cylinders and outrigger pads
<b>SWING</b>	3 slewing gears
<b>HOIST</b>	Axial piston motor with planetary gear and brake, DRI indicator, hoist camera and light
<b>CAB</b>	<p>Superstructure Cab: Full vision aluminum cab, tiltable to 20°</p> <p>Driver's Cab: Two-man left hand drive, driver seat with pneumatic suspension, safety glass, AC, two rotating beacons, fire extinguisher</p>
<b>COUNTERWEIGHT</b>	70 t (154,300 lb), hydraulic removal system
<b>OPTIONAL EQUIPMENT</b>	<ul style="list-style-type: none"> <li>11/18 m (36/59 ft) bifold swingaway</li> <li>26/34 m (85/112 ft) boom extension</li> <li>Aux hoist</li> <li>Aux boom nose</li> <li>Aux hoist</li> <li>Superstructure air conditioning system</li> <li>MAXbase variable outrigger positioning</li> <li>Reverse camera system</li> </ul>

For additional information, please contact **Bruce Austin** at (443) 962-0746 or [Jaime.Cook@mgxequipment.com](mailto:Jaime.Cook@mgxequipment.com).

*Crane available subject to prior sale.*