

MANITOWOC MLC150-1

Capacity: 150 t (165 USt)



Crane Specifications

ENGINE	Cummins Model QSB6.7 Tier 4f/EU Stage V diesel engine, rated 240 kW (325 HP) at 2200 RPM
COUNTERWEIGHT	Upperworks counterweight attached to rotating bed. Carbody counterweight boxes attached to carbody.
SELF-ERECT OPTION	Includes carbody jacking cylinders with pads, self-erect cylinder fitted to live mast assembly and synthetic lifting slings.
DRUMS	Two 750 mm (29.5") drums.
OPERATOR'S CAB	Fully enclosed, insulated galvanized steel; sliding door, large safety glass windows, signal horn, cab space heater, front and roof windshield wipers, AC, dome light, sun visor and shade, fire extinguisher, fan.
CONTROLS	The Crane Control System offers a user-friendly interface, full graphic display mounted vertically for better visibility, a jog dial for easier data input and ergonomic joysticks. RCL/RCI is standard.
CRAWLER ASSEMBLIES	8 m (26'3") crawler assemblies independently powered. Max ground speed 2.1 km/hr (1.3 mph).



For additional information, please contact
Bruce Austin at (443) 962-0746 or
Jaime.Cook@mgxequipment.com.
Crane available subject to prior sale.