

GROVE GRT540

Capacity: 40 t (40 USt)

Boom Length: 9.8 m - 31 m (32 ft - 102 ft)



GROVE®



Crane Specifications	
BOOM	• 9.8 m - 31 m (32 ft - 102 ft) four-section full-power boom • 33.6 m (110.2 ft) max tip height • -3° - 79° boom elevation
ENGINE	129 kW (173 HP) Cummins B6.7L diesel
TRANSMISSION	Rangeshift with six forward and six reverse speeds
OUTRIGGERS	Four hydraulic telescoping single-stage double box beams, three positions (0%, 50%, fully extended) Outrigger monitoring system (OMS)
SWING	360-degree continuous rotation
HOIST	Grooved drum, two speed power up and down with automatic multi-disc brake
LOAD MOMENT AND INDEPENDENT ANTI-TWO BLOCK	RCL, load moment and anti-two block system with audio-visual warning and control lever lockout
COUNTERWEIGHT	3,992 kg (8,800 lb)
MISCELLANEOUS STANDARD EQUIPMENT	Aluminum decking, dual rear-view mirrors, hook block tie-down, electronic backup alarm, front stowage well, hot water cab heater/defroster, cab AC, multi-function meter, AV warning system, combination lift/tie-down towing lugs, coolant sight level indicator and hoist access platform, coolant sight level indicator and hoist access platform

For additional information, please call
844-DIAL-MGX.

Crane available subject to prior sale.